

IN THE CLAIMS

The following is a complete list of the claims now pending; this listing replaces all earlier versions and listings of the claims.

- F1
- ggg
G1
1. ~~(Currently Amended)~~ ~~An image processing apparatus comprising:~~
- ~~a communicator for performing two-way communications with an image output unit that includes an update unit for updating condition information indicating a condition of the image output unit and a memory for storing the condition information, wherein the condition information, used for calibration, is obtained by forming color patches and measuring colors on the color patches;~~
 - ~~an input unit for inputting an image output instruction;~~
 - ~~an acquisition unit for acquiring the condition information stored in the image output unit by utilizing the a two-way communications communication, in response to the image output instruction; and~~
 - ~~an image processor for performing image processing of image data in accordance with the condition information acquired by said acquisition unit, wherein said image processor decreases a bit length for each pixel of the processed image data processed using the condition information and then outputs the bit-length-decreased image data to the image output unit via a communication line.~~
2. (Previously Amended) The apparatus according to claim 1, wherein the image output unit further includes:
- ~~an engine unit; and~~
 - ~~a condition acquisition unit for automatically acquiring the condition~~

~~information in accordance with a change in status of the engine unit, wherein the acquired condition information is stored in the memory.~~

3. (Previously Amended) The apparatus according to claim 1, wherein the condition information is a measurement result of a plurality of patches outputted by the image output unit.

4. (Previously Amended) The apparatus according to claim 1, wherein said image processor converts image data into multi-valued data corresponding to a type of a recording medium used in the image output unit, and performs image processing in accordance with the condition information.

5. (Cancelled)

6. (Currently Amended) The apparatus according to claim 1, further comprising:
a user interface for setting whether or not the image processing is to be done in accordance with the condition information.

7. (Currently Amended) An image processing apparatus connected, via a communication network, with a host computer and a plurality of image output units, each image output unit having adapted to perform a function of updating condition information, for calibration, of the image output unit, the condition information being

~~obtained by forming color patches and measuring colors on the color patches, said~~

apparatus comprising:

an input unit for inputting the condition information updated by the plurality of image output units;

a memory for storing the inputted condition information in association with each of the plurality of image output units;

a transmitter for transmitting the stored condition information to the host computer in accordance with a request for acquiring the condition information issued by the host computer; and

a management unit for managing an image output job of the host computer, wherein the condition information is obtained by forming color patches and measuring colors on the color patches,

wherein the host computer performs image processing of image data in accordance with the condition information transmitted by said transmitter,

wherein the host computer decreases a bit length for each pixel of the processed image data processed using the condition information and then outputs the bit-length-decreased image data to the image output unit via a communication line, and

wherein each of the plurality of image output units outputs an image based on the image data processed by the host computer.

8. (Previously Amended) The apparatus according to claim 7, further comprising a second management unit for managing an image output job for an image output unit.

9. (Previously Amended) The apparatus according to claim 7, wherein each of the plurality of image output units comprises:

an engine unit;
a condition acquisition unit for automatically acquiring the condition information in accordance with a change in status of the engine unit; and
a memory for storing the acquired condition information.

10. (Currently Amended) The apparatus according to claim 7, further comprising:

a user interface for setting whether or not image processing is to be done in accordance with the condition information.

11. (Currently Amended) An image processing method for performing image processing in a network system to which an image output apparatus, a server, and a network terminal are connected, said method comprising:

in the image output apparatus:

a condition measurement step, of updating condition information, for calibration, by forming color patches and measuring colors on the color patches; and
a notification step, of notifying the server of the updated condition information,

in the server:

a storage step, of storing the updated condition information notified from the image output apparatus in correspondence with a type of the image output apparatus; and

~~a management step, of managing an image output job, and~~

in the network terminal:

~~an input step, of inputting an image output instruction of a user;~~

~~an acquisition step, of acquiring the updated condition information stored in the server in response to the image output instruction; and~~

~~an image processing step, of performing image processing using an image processing condition in accordance with the updated condition information, wherein said image processing step decreases a bit length for each pixel of the image data processed using the condition information and then decreasing bit length for each pixel of the processed image data and outputting the bit-decreased outputs the bit-length-decreased image data to the image output unit via a communication line.~~

12. (Currently Amended) An image processing method performed in a server connected, via a communication network, with a host computer and a plurality of image output units, each image output unit having adapted to perform a function of updating condition information, for calibration, indicating a condition of the image output unit, said method comprising:

~~an input step, of inputting an image output instruction;~~

~~an acquisition step, of acquiring the condition information stored in the image output unit by utilizing two-way communications, in response to the image output instruction; and~~

~~an image processing step, of performing image processing of image data in accordance with the condition information acquired in said acquisition step, wherein said image processing step decreases a bit length for each pixel of the processed~~

~~image data processed using the condition information and then outputs the bit-decreased~~
~~bit-length-decreased image data to the image output unit via a communication line.~~

13. (Currently Amended) An image processing method performed in a server connected, via a communication network, with a host computer and a plurality of image output units, each image output unit having adapted to perform a function of updating condition information, for calibration, of the image output unit, said method comprising:

an input step, of inputting the condition information updated by the plurality of image output units;

a storage step, of storing the inputted condition information in association with each of the plurality of image output units;

a transmission step, of transmitting the stored condition information to the host computer in accordance with a request for acquiring the condition information issued by the host computer; and

a management step, of managing an image output job of the host computer,

wherein the condition information is obtained by forming color patches and measuring colors on the color patches,

wherein the host computer performs image processing of image data in accordance with the condition information transmitted in said transmission step,

wherein the host computer decreases a bit length for each pixel of the processed image data processed using the condition information and then outputs the

~~bit-decreased bit-length-decreased image data to the image output unit via a~~
communication line, and

wherein each of the plurality of image output units outputs an image based on the image data processed by the host computer.

14. (Currently Amended) A computer-readable storage medium that stores a program for implementing, by a computer, an image processing method, the program comprising:

code for a communication step, of performing two-way communications with an image output unit having that includes an update unit for updating condition information indicating a condition of the image output unit and a memory for storing the condition information, wherein the condition information, used for calibration, is obtained by forming color patches and measuring colors on the color patches;

code for an input step, of inputting an image output instruction;
code for an acquisition step, of acquiring the condition information stored in the image output unit by utilizing the two-way communications, in response to the image output instruction; and

code for an image processing step, of performing image processing of image data in accordance with the condition information acquired by the acquisition step,

wherein said image processing function decreases a bit length for each pixel of the ~~processed~~ image data processed using the condition information and then outputs the ~~bit-decreased bit-length-decreased~~ image data to the image output unit via a communication line.

15. (Currently Amended) A computer-readable storage medium that stores a program for an image processing method performed by a server connected, via a communication network, with a host computer and a plurality of image output units, each image output unit having adapted to perform a function of updating condition information, for calibration, of the image output unit, the program comprising:

code for an input step, of inputting the condition information updated by the plurality of image output units;

code for a storage step, of storing the inputted condition information in association with each of the plurality of image output units;

code for a transmission step, of transmitting the stored condition information to the host computer in accordance with a request for acquiring the condition information issued by the host computer; and

code for a management step, of managing an image output job of the host computer,

wherein the condition information is obtained by forming color patches and measuring colors on the color patches,

wherein the host computer performs image processing of image data in accordance with the condition information transmitted by the transmission step,

wherein the host computer decreases a bit length for each pixel of the ~~processed~~ image data processed using the condition information and then outputs the ~~bit-decreased~~ bit-length-decreased image data to the image output unit via a communication line, and

wherein each of the plurality of image output units outputs an image based on the image data processed by the host computer.